



TECHNICAL SPECIFICATION

	CX-3600	CX-4000
Rated Power (Stereo 8Ω / ch.)	1100W	1300W
Rated Power (Stereo 4Ω / ch.)	1800W	1950W
Rated Power (Stereo 2Ω / ch.)	2200W	2600W
Rated Power (Bridge Mono 8Ω)	3600W	3900W
Rated Power (Bridge Mono 4Ω)	4400W	5200W
Frequency Response	20Hz - 20KHz, +0/-0.3dB	20Hz - 20KHz, +0/-0.3dB
THD+N	< 0.03% @ 8Ω 1KHz	< 0.03% @ 8Ω 1KHz
S/N Ratio	> 93dB	> 93dB
Slew Rate	44V/us	44V/us
Damping Factor	> 300	> 300
Crosstalk	> 70dB @ 8Ω 1KHz	> 70dB @ 8Ω 1KHz
Input Impedance	20KΩ balanced / 10KΩ unbalanced	20KΩ balanced / 10KΩ unbalanced
Input Sensitivity	0.775V / 1.0V / 1.4V	0.775V / 1.0V / 1.4V
Height	3U	3U
Gross Weight	43 Kg.	41 Kg.

CX 3600 REAR PANEL



CX 4000 REAR PANEL



<http://www.nts-solution.com>

All features & specifications are subjected to change without notice.

NTS บริษัท เอ็นทีเอส อิเล็กทรอนิกส์ โซลูชั่น จำกัด
NTS Electronic Solution Co., Ltd.

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600

โทรศัพท์: 0-2438-7023-4, 0-2437-7639 โทรสาร: 0-2437-1897

<http://www.nts-solution.com> E-mail: nts@nts-solution.com

1439-1441 Charoenakorn Rd. Banglumpoolang Klongsan Bangkok 10600, Thailand

Tel: (+66-2) 438-7023-4, (+66-2) 437-7639 Fax: (+66-2) 437-1897