GS-SERIES

MIXER WITH 16 PRESETS DSP EFFECT

GS-8FX : 8 Channel (4 Mono/2 Stereo) with 16 Presets DSP Effect

GS-12FX : 12 Channel (8 Mono/2 Stereo) with 16 Presets DSP Effect

TECHNICAL SPECIFICATION

- +48V phantom power
- Build in pre amplifier for mic
- Dual group main output control
- 3 band EQ for each channel
- Low cut for all mono channel
- With reduce noise function for karaoke
- Build in 16 DSP effector
- Record earphone monitor output
- Five band effect level monitor
- 2 group - 3 color 8 band level display
- FX foot switch

MAIN SPECIFICATION :

Channel Mic/Line ..... 8 CH : 4 Mono/2 Stereo [GS-8FX]
..... 12 CH : 8 Mono/2 Stereo [GS-12FX]

Total Harmoinc Distortion ..... ≤ 0.05%
Frequency Response ..... 5Hz-50kHz, +/-3dB
S/N Ratio ..... ≥ -103dB
Max Output ..... 4V Max
Input Sensitivity : Mic ..... -60dB
: Line ..... -40dB
: Effect Return ..... -40dB
: Aux in ..... -40dB
: Tape in ..... -40dB
Input EQ : High ..... +/-15dB, 12kHz
: Mid ..... +/-15dB, 250Hz-6KHz
: Low ..... +/-15dB, 60Hz
Phantom Power ..... +48V
Effector ..... Build in 16 DSP Effector
Power Consumption ..... 35W [GS-8FX]
..... 45W [GS-12FX]
Size [HxWxD] ..... 90 x 245 x 330 mm. [GS-8FX]
..... 90 x 353 x 330 mm. [GS-12FX]

http://www.nts-solution.com

All features & specifications are subjected to change without notice.

บริษัท เอ็นทีเอส อิเล็กทรอนิกส์ โซลูชั่น จำกัด
NTS Electronic Solution Co., Ltd.

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600
โทรศัพท์: 0-2438-7023-4, 0-2437-7639 โทรสาร: 0-2437-1897
http://www.nts-solution.com E-mail: nts@nts-solution.com
1439-1441 Charoennakorn Rd. Banglumpoolang Klongsan Bangkok 10600, Thailand
Tel: (+66-2) 438-7023-4, (+66-2) 437-7639 Fax: (+66-2) 437-1897