

# PA-SERIES

PASSIVE PORTABLE LOUDSPEAKER



## TECHNICAL SPECIFICATION

PASSIVE PORTABLE LOUDSPEAKER

PA-SERIES

	PA-15A	PA-12A	PA-10A
Frequency-response	45Hz ~ 18KHz	50Hz ~ 18KHz	50Hz ~ 18KHz
RMS power handling	250W RMS	200W RMS	125W RMS
Peak power handling	500W PEAK	400W PEAK	250W PEAK
Nominal impedance	8Ω	8Ω	8Ω
Sensitivity [1w/1m]	98dB	97dB	96dB
Connections	2-speakon	2-speakon	2-speakon
Low frequency	15" woofer aluminium frame	12" woofer aluminium frame	10" woofer aluminium frame
High frequency	44 mm. titanium driver	44 mm. titanium driver	34 mm. titanium driver
Dimension [HxWxD]	700x500x360 mm.	620x410x300 mm.	510x350x310 mm.
Weight	18 kg.	15 kg.	11 kg.

<http://www.nts-solution.com>

All features & specifications are subjected to change without notice.

**NTS** บริษัท เอ็นทีเอส อิเล็กทรอนิกส์ โซลูชั่น จำกัด  
NTS Electronic Solution Co., Ltd.

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600

โทรศัพท์: 0-2438-7023-4, 0-2437-7639 โทรสาร: 0-2437-1897

<http://www.nts-solution.com> E-mail: [nts@nts-solution.com](mailto:nts@nts-solution.com)

1439-1441 Charoennakorn Rd. Banglumpoolang Klongsan Bangkok 10600, Thailand

Tel: (+66-2) 438-7023-4, (+66-2) 437-7639 Fax: (+66-2) 437-1897