

PC-SERIES

PASSIVE/ACTIVE PORTABLE LOUDSPEAKER

NTS



TECHNICAL SPECIFICATION

PC-12 / PC-15 : PASSIVE PORTABLE LOUDSPEAKER

PC-12A / PC-15A : ACTIVE PORTABLE LOUDSPEAKER

PC-12/PC-12A

Frequency-response	45Hz ~ 20KHz
RMS power handling	250W RMS
Peak power handling	500W PEAK
Nominal impedance	8Ω
Sensitivity [1w/1m]	96dB
Connections	2 x speakon
Low frequency	12" woofer
High frequency	34 mm. titanium driver
Dimension [HxWxD]	660x390x357 mm.
Weight	15.5 kg. (PC-15) 19.5 kg. (PC-15A)

POWER AMPLIFIER (PC-12A)

LF Power	200W RMS
HF Power	50W RMS
Max SPL	125dB
Equalization	2 band EQ +/-15dB
Connections	1/4" phone (mic I/P), XLR (line I/P)
Frequency Response	20Hz ~ 20KHz
Crossover Frequency	2.5KHz

PC-15/PC-15A

Frequency-response	45Hz ~ 20KHz
RMS power handling	250W RMS
Peak power handling	500W PEAK
Nominal impedance	8Ω
Sensitivity [1w/1m]	98dB
Connections	2 x speakon
Low frequency	15" woofer
High frequency	34 mm. titanium driver
Dimension [HxWxD]	790x475x420 mm.
Weight	25.5 kg. (PC-15) 30 kg. (PC-15A)

POWER AMPLIFIER (PC-15A)

LF Power	200W RMS
HF Power	50W RMS
Max SPL	128dB
Equalization	2 band EQ +/-15dB
Connections	1/4" phone (mic I/P), XLR (line I/P)
Frequency Response	20Hz ~ 20KHz
Crossover Frequency	2.5KHz

<http://www.nts-solution.com>

All features & specifications are subjected to change without notice.

NTS

บริษัท เอ็นทีเอส อิเล็กทรอนิกส์ โซลูชั่น จำกัด
NTS Electronic Solution Co., Ltd.

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600

โทรศัพท์: 0-2438-7023-4, 0-2437-7639 โทรสาร: 0-2437-1897

<http://www.nts-solution.com> E-mail: nts@nts-solution.com

1439-1441 Charoennakorn Rd. Banglumpoolang Klongsan Bangkok 10600, Thailand

Tel: (+66-2) 438-7023-4, (+66-2) 437-7639 Fax: (+66-2) 437-1897