

PASSIVE PORTABLE LOUDSPEAKER



TECHNICAL SPECIFICATION

PD-12 : PASSIVE PORTABLE LOUDSPEAKER

PD-12

Frequency response	45Hz ~ 18KHz
Sensitivity [1w/1m]	96dB
RMS power handling	200W RMS
Voice coil	2.5" KSV
Magnet	50 Oz.
Low frequency	12" Woofer
High frequency	1.34" (34 mm.)
Nominal impedance	8Ω

PD-15 : PASSIVE PORTABLE LOUDSPEAKER

PD-15

Frequency response	40Hz ~ 18KHz
Sensitivity [1w/1m]	98dB
RMS power handling	300W RMS
Voice coil	3" KSV
Magnet	60 Oz.
Low frequency	15" Woofer
High frequency	1.75" (44 mm.)
Nominal impedance	8Ω

<http://www.nts-solution.com>

All features & specifications are subjected to change without notice.



บริษัท เอ็นทีเอส อิเล็กทรอนิกส์ โซลูชั่น จำกัด
NTS Electronic Solution Co., Ltd.

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600

โทรศัพท์: 0-2438-7023-4, 0-2437-7639 โทรสาร: 0-2437-1897

<http://www.nts-solution.com> E-mail: nts@nts-solution.com

1439-1441 Charoennakorn Rd. Banglumpoolang Klongsan Bangkok 10600, Thailand

Tel: (+66-2) 438-7023-4, (+66-2) 437-7639 Fax: (+66-2) 437-1897