

JX-8A / JX-10AU

ACTIVE PORTABLE LOUDSPEAKER



ACTIVE PORTABLE ABS LO



JX-8A
8 inch
WOOFER



JX-10AU
10 inch
WOOFER



TECHNICAL SPECIFICATION

JX-8A : ACTIVE PORTABLE LOUDSPEAKER

JX-8A

Frequency response	60Hz ~ 18KHz
Sensitivity [1w/1m]	92dB
Power handling	100W
Voice coil	1.5" KSV
Magnet	30 Oz.
Low frequency	8" Woofer
High frequency	1" (25 mm.)
Nominal impedance	8Ω

POWER AMPLIFIER

Rated power	100W
AC Main	220 VAC, 50 Hz

JX-10AU : ACTIVE PORTABLE LOUDSPEAKER
with USB SLOT / LCD SCREEN / REMOTE

JX-10AU

Frequency response	50Hz ~ 18KHz
Sensitivity [1w/1m]	93dB
Power handling	150W
Voice coil	2" KSV
Magnet	40 Oz.
Low frequency	10" Woofer
High frequency	1" (25 mm.)
Nominal impedance	8Ω

POWER AMPLIFIER & USB SLOT / LCD SCREEN / REMOTE

Rated power	150W
AC Main	220 VAC, 50 Hz

<http://www.nts-solution.com>

All features & specifications are subjected to change without notice.



บริษัท เอ็นทีเอส อิเล็กทรอนิกส์ โซลูชั่น จำกัด
NTS Electronic Solution Co., Ltd.

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600

โทรศัพท์: 0-2438-7023-4, 0-2437-7639 โทรสาร: 0-2437-1897

<http://www.nts-solution.com> E-mail: nts@nts-solution.com

1439-1441 Charoennakorn Rd. Banglumpoolang Klongsan Bangkok 10600, Thailand

Tel: (+66-2) 438-7023-4, (+66-2) 437-7639 Fax: (+66-2) 437-1897