

# JX-12AU / JX-15AU

ACTIVE PORTABLE LOUDSPEAKER



## ACTIVE PORTABLE ABS LOUDSPEAKER



**JX-12AU**  
12 inch  
WOOFER



**JX-15AU**  
15 inch  
WOOFER

### TECHNICAL SPECIFICATION

12"/15" ACTIVE PORTABLE LOUDSPEAKER  
with USB SLOT / LCD SCREEN / REMOTE CONTROL

#### JX-12AU

Frequency response .....	45Hz ~ 18KHz
Sensitivity [1w/1m] .....	96dB
Power handling .....	200W
Voice coil .....	2.5" KSV
Magnet .....	50 Oz.
Low frequency .....	12" Woofer
High frequency .....	1.34" (34 mm.)
Nominal impedance .....	8Ω

#### POWER AMPLIFIER & USB SLOT / LCD SCREEN / REMOTE

Rated power .....	150W
AC Main .....	220 VAC, 50 Hz

#### JX-15AU

Frequency response .....	40Hz ~ 18KHz
Sensitivity [1w/1m] .....	98dB
Power handling .....	300W
Voice coil .....	3" KSV
Magnet .....	60 Oz.
Low frequency .....	15" Woofer
High frequency .....	1.75" (44 mm.)
Nominal impedance .....	8Ω

#### POWER AMPLIFIER & USB SLOT / LCD SCREEN / REMOTE

Rated power .....	180W
AC Main .....	220 VAC, 50 Hz

<http://www.nts-solution.com>

All features & specifications are subjected to change without notice.



บริษัท เอ็นทีเอส อิเล็กทรอนิกส์ โซลูชั่น จำกัด  
NTS Electronic Solution Co., Ltd.

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600

โทรศัพท์: 0-2438-7023-4, 0-2437-7639 โทรสาร: 0-2437-1897

<http://www.nts-solution.com> E-mail: [nts@nts-solution.com](mailto:nts@nts-solution.com)

1439-1441 Charoennakorn Rd. Banglumpoolang Klongsan Bangkok 10600, Thailand

Tel: (+66-2) 438-7023-4, (+66-2) 437-7639 Fax: (+66-2) 437-1897