

# HIGH FREQUENCY COMPRESSION DRIVER

Mounting Type :: Screw Thread / Bolt On



**PH-340**



**PH-440 / PH-440A**



**PH-510 / PH-510A**

### TECHNICAL SPECIFICATION

	PH-340	PH-440 / PH-440A	PH-510 / PH-510A
Mounting Type	Screw thread	Screw thread / Bolt on	Screw thread / Bolt on
Voice Coil	1.34" (34 mm.)	1.75" (44 mm.)	2" (51 mm.)
Magnet	13 Oz. (90 x 65 x 15 mm.)	22.6 Oz. (115 x 70 x 15 mm.)	35 Oz. (135 x 74 x 17 mm.)
Impedance	8Ω	8Ω	8Ω
Frequency Response	600Hz - 18KHz	600Hz - 18KHz	600Hz - 18KHz
Power	40W	60W	80W

<http://www.nts-solution.com>

All features & specifications are subjected to change without notice.



บริษัท เอ็นทีเอส อิเล็กทรอนิกส์ โซลูชั่น จำกัด  
NTS Electronic Solution Co., Ltd.

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600

โทรศัพท์: 0-2438-7023-4, 0-2437-7639 โทรสาร: 0-2437-1897

<http://www.nts-solution.com> E-mail: [nts@nts-solution.com](mailto:nts@nts-solution.com)

1439-1441 Charoennakorn Rd. Banglumpoolang Klongsan Bangkok 10600, Thailand

Tel: (+66-2) 438-7023-4, (+66-2) 437-7639 Fax: (+66-2) 437-1897